


REV.	ECN. NO.	APPD.
A	DWG. REL.	

NOTE:

1. Material & Finish See Table;

2. Circuit Diagram For Switch



3. Characteristic:

- 3-1.Current Rating: 12V, 1A max.
- 3-2.Contact Resistance: 30mOhms max.(initial)
- 3-3.Insulation Resistance: 100MOhms? min./500VDC
- 3-4.Dielectric Withstanding Voltage: 500VAC/1minute
- 3-5.Mating Force: 30N Max, Withdrawal Force: 3N Min.;
- 3-6.Durability: 5,000 Cycles

3-7.Operating Temperature:-25°C to+85°C

4. Critical Dimensions Marked "▼" Should Check By QC.

AAR43-04 \* \* \* \* \*

- ① HOUSING COLOR  
0: WHITE
- ② CONTACT GOLD PLATED  
1: G/F
- ③ DIM A  
1: DIM A=5.70±0.05  
2: DIM A=5.95±0.05
- ④ PACKAGE  
3: BAG
- ⑤ MARK  
0: NO MARK

Item	Part Name	Material	Description
7	Sleeve	Copper Alloy	Nickel Plated
6	Housing	Thermoplastics	White,UL94V-0
5	Contact 5	Copper Alloy	Tin Plated on Overall; Nickel Under Plated.
4	Contact 4	Copper Alloy	
3	Contact 3	Copper Alloy	Gold Flash on Contact Area; Tin Plated on Solder Tails; Nickel Under Plated Overall.
2	Contact 2	Copper Alloy	
1	Contact 1	Copper Alloy	

INTENDED USE	QTY	HUNG TA H.T.ENTERPRISE CO.,LTD	
PART NO. AAR43-04*****	FINISH	FILE NO. C-AAR43-00-A0	TITLE: Ø3.5mm Audio Jack For Cable
TOLERANCES .X ± 0.35 .X ± .XX± 0.25 .XX±	MATL	APPD: HONDA 20170105 CHKD: LONG 20170105 DR: LONG 20170105	DWG NO.: C-AAR43-00-A0 REV. A
		SCALE 1:1	SHEET 1 OF 1