



SPECIFICATION
MATERIAL
 Insulator: Thermal Plastic UL94V-0
 Contacts: Copper alloy
 Shell: Steel
CONTACT PLATING
 Underplate: 50u"~150u" Nickel
 Salt fog: 8 hours
 Contact area: Gold flash
 Solder tails area: 100u" Min. Tin(Lead Free)
ELECTRICAL
 Operation voltage: 250V Max.
 Current rating: 2.5 Amps Max.
 Contact resistance: 25 mohms initial
 Insulation resistance: 3000 Mohms min @ 500 VDC
 Dielectric withstanding voltage: 500 VAC / minute
 Temperature range: -55°C TO +85°C
 Mating cycles: 500 insertions
 Part no.

GENERAL TOLERANCE				HT HUNG TA H.T.ENTERPRISE CO.,LTD			
General		Angle		TITLE:			
X.	±0.38	X°	±3.0°	HDD - SUB 15 PIN W/AT LOGO SLIM ROHS (046)			
.X	±0.30	.X°	±2.0°	PART NO:			
.XX	±0.25	.XX°	±1.0°	K-DOR104-15YAN00			
.XXX	±0.10	.XXX°	±0.5°	UNIT:mm		SCALE:1:1	
No.		DATE		DESCRIPTION		APPROVE	
1		2		3		4	

CHECKED				APPROVED				REV:A	
No.		DATE		DESCRIPTION		APPROVE		REV:A	
1		2		3		4		11	